



CE	NMC Polska, ul. Pyskownicza 15, PL - 41807 Zabrze	Thermal insulation products for building equipment and industrial installations
	14	Reaction to fire (3mm) : Bs3d0
	NB 1454, NB 1486, NB 0751, NB 1498, NB 0919	Temperature range: from -30°C to +95°C
	EN 14304-A1:2013	Thermal conductivity: 0,040 W/mK at 40°C
		DOP No.: W4-FEE-304 (see website for complete DOP: www.nmc.eu/dop)

INSUL TAPE

Product features

- Dimension: 3 mmx 50 mm (15 m length)
- Thermal conductivity (EN ISO 12667):
 - 0,033 W/mK at -50 °C
 - 0,034 W/mK at -30 °C
 - 0,036 W/mK at 0 °C
 - 0,039 W/mK at 40 °C
 - 0,041 W/mK at 70 °C
- Fire performance: Bs3d0 (EN 13501-1)
- Temperature range: -50 °C to 95 °C (EN 14707)
- Processing temperature: $\geq +5$ °C
- See website for Declaration of Performance:
www.nmc-insulation.com

Application area

- Heating and plumbing
- Air conditioning
- Cooling systems



NMC (uk) Ltd.

Tafarnaubach Industrial Estate · UK - NP22 3AA Tredgar, South Wales

Phone: +44 1495 713266 · Fax: +44 1495 713277

Email: enquiries@nmc-uk.com

www.nmc-insulation.com

