

Part-No.

Type

167174

FN035-4EK.0F.V7P3

Axial fan with sickle blades
with guard grille for short bell mouth
Type:FN035-4EK.0F.V7P3
1~ 230V $\pm 10\%$ 50Hz P1 150W
0,65A DI=35% 1390rpm 3uF/400V 70°C
1~ 230V $\pm 10\%$ 60Hz P1 230W
1,0A DI=15% 1520rpm 3uF/400V 60°C
IP54 THCL 155
ErP conform 2015
N=40,9
statA=29,2%
Terminal box K05
Mounted on Stator.
Capacitor included in the terminal box.
wiring diagram: 1360-104XA
Rating plate: 1x fixed
Fitting position H/Vu/Vo.
Motor protection: thermal contact
minimal operating temperature -25 degree
Moisture and hot climate protection.
ball bearing with long-time lubrication.
impeller made of High Performance Composite Material.
Stator 1 coat paint RAL 9005 (jet black) resistance class 1 (L-TI-0596)
Rotor 1 coat paint RAL 9005 (jet black) resistance class 1 (L-TI-0596)
Blades unpainted black
Motor suspension powder-coated RAL 9005 (jet black)
resistance class 2 (L-TI-0585).
ring grill
All connecting elements in stainless steel.
