

KKJ HB BOX

Model	Surface	Tube volume	Capacity R404A $\Delta T=15K$		Fans			
			S	L	Quantity	Diameter	Air volume flow	
			1/230V AC 50Hz 1400rpm	1/230V AC 50Hz 900 rpm			1400 rpm 4 pole	900 rpm 6 pole
m ²	dm ³	kW	kW	n°	mm	m ³ /h	m ³ /h	
030630N1	6,19	0,8	3,12	2,70	1	Ø300	2150	1670
051230N1	11,92	1,2	4,85	3,95	1	Ø300	2080	1530
061235N1	12,08	1,5	6,17	5,18	1	Ø350	2800	2120
091740N2	16,67	1,8	8,58	7,41	1	Ø400	4220	3270
112145N3	20,74	2,7	10,87	8,87	1	Ø450	5000	3610
152550N4	25,00	3,2	14,84	11,83	1	Ø500	7725	5420
183740N5	37,21	4,7	18,35	16,00	2	Ø400	8590	6760
213845N6	38,20	4,8	20,66	16,96	2	Ø450	9890	7110
234645N7	46,48	5,8	22,81	18,71	2	Ø450	10160	7400
112440T2	23,82	2,6	10,73	8,75	1	Ø400	3950	2900
143045T3	29,67	3,8	13,49	10,69	1	Ø450	4750	3370
173250T4	32,20	4,1	17,00	13,43	1	Ø500	6810	4840
235440T5	53,98	6,6	23,50	19,28	2	Ø400	8140	6130
265545T6	55,45	6,8	26,01	20,53	2	Ø450	9350	6610
296945T7	68,69	8,6	28,86	22,91	2	Ø450	9790	7030



Model	Dimensions							Connections	
	L	H	W	LT	LC	W1	W2	Input	Output
	mm	mm	mm	mm	mm	mm	mm	mm/"	mm/"
030630N1	900	530	500	495	350	400	360	1/2	1/2
051230N1	900	530	500	495	350	400	360	1/2	1/2
061235N1	900	530	530	495	350	400	360	1/2	1/2
091740N2	1020	670	640	700	430	510	470	1/2	1/2
112145N3	1220	670	640	1000	510	510	470	1/2	1/2
152550N4	1220	720	640	1000	510	510	470	1/2	1/2
183740N5	1220	1210	640	1000	510	510	470	3/4	5/8
213845N6	1220	1210	640	1000	510	510	470	3/4	5/8
234645N7	1220	1210	640	1000	510	510	470	3/4	5/8
112440T2	1020	670	640	700	430	510	470	1/2	1/2
143045T3	1220	670	640	1000	510	510	470	1/2	1/2
173250T4	1220	720	640	1000	510	510	470	1/2	1/2
235440T5	1220	1210	640	1000	510	510	470	3/4	5/8
265545T6	1220	1210	640	1000	510	510	470	3/4	5/8
296945T7	1220	1210	640	1000	510	510	470	3/4	5/8

	1	2	3	4	5
	03	06	30	N	1

1	Capacity	3 kW - 29 kW
2	Surface	6 m ² - 68 m ²
3	Fans	Ø300 - Ø500
4	Execution	N - normal T - tropical
5	Size of the unit	1 - 7

