

SSUC 250 series

Model	Capacity SC2	Air flow	Air throw	Surface	Fans	Length
	kW	m3/h	m	m2	n°	mm
<i>Fin space</i> 4 mm						
SSUC1250DA1-E	0,57	423	4	3,0	1	493
SSUC1250DA2-E	0,88	553	5	4,0	1	693
SSUC1250DA3-E	1,40	642	5	6,0	1	893
SSUC1250DB3-E	1,82	718	6	8,0	1	893*
SSUC2250DA4-E	2,11	983	4	8,0	2	1093
SSUC2250DB4-E	2,56	1161	5	10,0	2	1093*
SSUC3250DA5-E	2,83	1411	4	11,0	3	1493
SSUC3250DB5-E	3,80	1693	5	14,0	3	1493*

<i>Fin space</i> 7 mm						
SSUC1250GA1-E	0,42	441	4	2,0	1	493
SSUC1250GA2-E	0,63	584	5	3,0	1	693
SSUC1250GA3-E	0,97	675	6	3,0	1	893
SSUC1250GB3-E	1,34	749	6	5,0	1	893*
SSUC2250GA4-E	1,66	1048	5	4,0	2	1093
SSUC2250GB4-E	1,99	1229	5	6,0	2	1093*
SSUC3250GA5-E	2,27	1509	5	6,0	3	1493
SSUC3250GB5-E	2,73	1781	5	8,0	3	1493*

Fans: Ø250, 230V / 1P / 50Hz, 1300RPM, 65W, 0,45A

	1	2	3	4	5	6	7
	SSUC	1	250	D	A	1	E

1	Product code	SSUC				
2	N° fans	1	2	3		
3	Fans	Ø 250				
4	Fins spacing	D - 4 mm		G - 7 mm		
5	Modul	A - 3 rows		B - 4 rows		
6	Length	1 - 493 mm	2 - 693 mm	3 - 893 mm	4 - 1093 mm	5 - 1493 mm
7	Defrosting	A - air defrost		E - el. defrost		

