Acknowledged globally





## FLARE-e-Z

## Item Number 4689045

The 45° flare tool FLARE-e is ideal for hard-to-reach places due to its low weight and compact design. The powerful battery with highquality Samsung cells allows up to 135 flaring operations per charge.

It is protected against overcharging, discharging, overheating, overcurrent, and short-circuit, ensuring its longevity and user safety. The delivery includes a sturdy plastic case and a deburrer as well as standard 6 inch flaring clamps for various pipe diameters (1/4" to 3/4"). For maximum work safety, the flare clamps can be securely locked.

Furthermore, a microswitch allows the device to start only when the flare clamp is installed. Even if the flaring process has already started, pressing the main switch repeatedly can cancel the flaring process.

The integrated lighting provides a clear view even in dark corners. The device is securely stored in the robust case along with the battery, charger, and deburrer.

- Precise and quick 45° flanging
- Light and compact: ideal for tube processing in hard-to-reach areas
- Includes 6 inch flaring clamps: 1/4", 5/16", 3/8", 1/2", 5/8", 3/4"
- High-performance battery: up to 135 flanges per battery charge
- Battery protection: protection against overcharging, discharging, overheating, overcurrent, and short circuit
- Maximum work safety: flanging clamps can be securely locked, and the FLARE-e only starts when the flanging clamp is installed
- Manual interruption of a started flanging process
- Integrated lighting: for best visibility even in dark corners
- Included charger: ensures fast charging
- Delivered in a sturdy plastic case including a deburrer

## **Technical Data**

**REFCO Manufacturing Ltd.** Industriestrasse 11 6285 Hitzkirch

Phone +41 41 919 72 82 Fax +41 41 919 72 83

info@refco.ch

Certificate ISO 9001 / ISO 14001

Acknowledged globally



Material	Steel   Aluminium   Plastics	
Colour	yellow (RAL 1023)   green (RAL 6026)   black (RAL 7021)	
RoHS Conformity	1	
Operating Temperature Range	5 °C - 40 °C	
Battery	included	
Packaging	Sturdy plastic case	
Tube Diameter 2	1/4, 5/16, 3/8, 1/2, 5/8, 3/4 "	

## Accessories

4688781	RFA-242-HD	Deburring tool
4688790	RFA-313-STYLO- HD	Deburring tool
4687051	RFA-209-STYLO- HD	Deburring tool