### Acknowledged globally





#### **VAMP-F**

#### **Item Number** 3004238

Quick and easy to install, highly versatile, exceptionally quiet, and the smallest of its kind on the market – this is the new condensate pump from the VAMP series. It combines innovative technology with practical benefits. Proven and interference-resistant optical sensor technology is paired with the reliable and silent operation of a diaphragm pump. In the development process, we focused on using as few components as possible to make installation and handling easy and fast for the user. The VAMP-F features an integrated reservoir and an optical level sensor, making it the smallest model on the market.

- Minimal space requirement: Standing at just 26 mm tall, it fits in even the tightest spaces
- Quiet operation: Thanks to advanced diaphragm pump technology and effective vibration dampening, the pump operates at less than 20 dB(A)
- Easy and quick installation: The posable hose serves as a reservoir replacement (with filter and adapter) for direct connection to the condensate tray
- Versatile applications: Suitable for wall-mounted units, ceiling units, and floor units
- Pump Capacity: Handles up to 22 liters per hour
- Discharge height: Capable of up to 15 meters
- Integrated switching power supply: Operates universally with input voltages ranging from 100-240
  VAC
- Optical level sensing technology: Reliable operation ensured by proven optical sensor
- Spare parts and accessories available
- Manufactured in Switzerland

### **Technical Data**

Material	Polyamide   FR-4
Colour	black
Standards	IEC 60335-1, IEC 60335-2-41, UL 778, CSA C22.2 #108
RoHS Conformity	Yes

6285 Hitzkirch

## Acknowledged globally



Туре	Diaphragm type
Operating Temperature Range	3 °C – 40 °C
Storage Temperature Range	-20 °C – 70 °C
Water Temperature Range	3 °C – 40 °C
Voltage	100 - 240 VAC
Frequency	50Hz/60Hz
<b>Protection Class</b>	II
Ingression Protection	IP44
<b>Energy Consumption</b>	6 W
Cable Length	1.8 m
Max. Flow Rate	22 l/h
Max. Suction Lift	2 m
Max. Discharge height	15 m
Noise Level	20 dB(A)
Alarm Relay	Normally-closed, failsafe 250 VAC, 5 A or 30 VDC, 5 A
Tube Diameter	6 mm
Packaging	Cardboard box
Scope of Supply	Pump. Posable hose with filter. Installation cable. Anti-siphon valve. Vent tube. Cable ties. Quick guide.
Max. Horizontal Run	75 m at 0 m head and 0 m suction
Power Consumption Idle	1.7 W

### Accessories

4689101	AP-mO/3	Adapter for VAMP condensate pumps, 3 pcs.
3004186	STAR-TUBE-600	Yellow star tube, 15m / 600 inches
4679160	PVC-TUBE	Plastic tube 6 mm, 30 meters, 1/4"
3004087	KIT-4087	Star tube with Siphon device
4678597	IN-LINE FILTER	Filter for condensate water

# Acknowledged globally



### **Spare Parts**

4689088	POSABLE-HOSE/4	Expandable posable hose with filter, 4 pcs.
3004065	HSG-4065/4	Siphon Device, 4 pieces