

17.05.2023

CONFORMITY DECLARATION

With this letter we certificate that our SPIRALATED PIPES product with code:

0016TU

0018TU

0020TU

are manufactured with below material technical data:

SOFT PVC:

TECHNICAL INFORMATION	TESTING METHOD	UNIT OF MEASURE	VALUE
Peso Specifico Specific Weight	ISO 1183	g/cm ³	1,255
Durezza Hardness	ISO 868	Shore	A 73
Carico di Rottura Tensile Strength	ISO 527	N/mm ²	18,5
Allungamento a Rottura Elongation at Break	ISO 527	%	300
Temp. di Irrig. a Torsione Cold Flex	ISO 458	°C	
Stabilità Termica Heat Stability	CEI 20-34/3-2	Minutes	30


Artiplastic Macos S.R.L.

Via Reiss Romoli 2/15 20019 Settimo Milanese (MI) Italy - Tel +39 02 3282129 - Fax +39 02 33500333

P. IVA e C.F. IT01346390154 Web site: www.artiplastic.it E-mail: info@artiplastic.it

RIGID PVC:

TECHNICAL INFORMATION	TESTING METHOD	UNIT OF MEASURE	VALUE
Peso Specifico Specific Weight	ISO 1183	g/cm ³	1,535
Grado Vicat (5 Kg.) Vicat Point (5 Kg.)	ISO 306	°C	81
Durezza Hardness	ISO 868	Shore D	80
Carico di Rottura Tensile Strength	ISO 527	N/mm ²	35
Carico di Snervamento Yield Point	ISO 527	N/mm ²	37,5
Allungamento a Rottura Elongation at Break	ISO 527	%	90
Modulo Elastico Flexural Modulus	ISO 178	N/mm ²	3400
Izod 23 °C Impact Strength	ISO 180	J/m	70
Infiammabilità V 0 Inflammability	UL 94		Class



Diam. Interno mm	Diam. Esterno mm	A = anima mat. Rigido mm	S = Spess. Copertura mat. Plast. mm	P = passo mm	Tolleranza sui diametri +/- %
16	20	2,5	0,8	6	2
18	22	2,6	0,8	6,8	2
20	24	2,6	0,8	7	2

With this document we declare total lack (or presence in minimum quantity as scripted in ROHS normative) of hazardous Substances in all the article of our production.

We herewith declare that our PVC compounds used to produce spiraled pipes system is properly added to resist to UV RAYS .

Best regards
ARTIPLASTIC MACOS SRL

Artiplastic Macos S.R.L.

Via Reiss Romoli 2/15 20019 Settimo Milanese (MI) Italy - Tel +39 02 3282129 - Fax +39 02 33500333

P. IVA e C.F. IT01346390154 Web site: www.artiplastic.it E-mail: info@artiplastic.it